

KENSINGTON GREEN FEATURES & SPECIFICATIONS THE JAMES

FIRST FLOOR (ENTRY WAY, FIRST BEDROOM, FIRST BATHROOM): • 7/16" OSB Sheathing

- Porcelain in Entry Hall
- First Bedroom Carpet (Pin drop Plush Carpet)
- Travertine or Porcelain Floors in bathroom and shower
- Quartzite Countertops
- Undermounted sink
- Moen Plumbing Fixtures
- Stained Oak Wood Steps up to Second Floor

SECOND FLOOR (KITCHEN, DINING, LIVING ROOM):

Solid Oak Floors throughout second floor

(finish to be determined)

- Wood Treads on Stairs
- Quartzite Countertops
- Mosaic backsplash
- Shaker Cabinets
- Powder Room with Pedestal Sink

THIRD FLOOR:

• Solid Oak Floors throughout third floor (finish to be determined)

- Wood Treads on Stairs
- Carpet throughout all bedrooms.

Master Bathroom:

- Porcelain Flooring in Bath and Shower
- Soaking tub
- Frameless Glass Shower
- Moen Plumbing Fixtures
- Undermounted Sink
- Quartzite Countertops
- Wood framed Mirrors
- Ebony Shaker Cabinets

Secondary Bathroom:

- Porcelain flooring and in shower
- Quartzite Countertops
- Undermounted Sink
- Moen Plumbing Fixtures
- Shaker Style Cabinets

MECHANICAL SPECIFICATIONS:

Foundation:

- Engineered Post Tension Foundation
- 3,000 psi concrete
- Engineered Building Pads

Frame and Cornice:

- Engineered Structural Framing
- 2"x4" Stud grade fire walls, every 16" (+or-) 0.C.
- Yellow pine ceiling joists 16" (+or-) 0.C.
- Yellow pine rafters, 16" (+or-) 0.C.
- 7/16" OSB Roof Decking with TechShield Radiant Barrier

- Engineered wood Trusses per floor
- 3/4" Tongue and Groove Subfloor
- Cem Plank Siding
- All subfloor is glued, nailed and screwed
- Anthony Power Beams
- Windstorm Per Plans and Codes

Windows:

• Aluminum frame, insulated (double pane), clear glass with Low-E

Ceiling Heights:

- 9' First Floor
- 10' and 22' Second Floor
- 10' Third Floor

Masonry:

- 3/4" Conventional Stucco System
- Sherwin Williams Conflex Elastomeric Coating

Roofina:

• 30 Year Roof Shingle

Air Conditioning and Heating:

- 5 Ton 14 SEER System
- Goodman Condensing Unit
- Goodman Furnace
- R-8/6 Silver Flex Duct in Attic
- Programmable thermostats

Electrical:

- All copper wiring throughout the house
- GFI safety switches where required by codes
- 150 AMP main electric panel
- All other electrical wiring as per floor plans
- Recessed Can Lighting
- Chrome Light Fixtures in baths, Brushed nickel in dining

Plumbing:

- CPVC vents and drain pipes
- Black steel pipes for gas
- Insulated Exposed Water Lines
- (1) Water Heater
- Moen EVA brushed Nickel Plumbing Fixtures

Insulation:

Area:	Material:	R-Value:	Thickness:
Exterior Walls	Batt	R-13	3.5″
Cold Floors	Batt	R-38	12″
Ceilings	Batt	R-19	6.25″
Attic	Blown	R-38	12″

IS THE ULTIM

Price, plans and specifications are subject to change without notice. All tile and counter tops are natural stone and dovary incolor. Not one piece is similar to another, colors and patterns may vary, and will not look exactly like samplesgiven.Allfinisheshavebeen pre-selected.Pleasen ote that finishes are subject to change without notice prior to contract being executed. Changes are at the builder's discretion and depend on pricing and availability.

