

AS OF JUNE 1st, 2016

STRUCTURAL:

Foundation

- Foundation Built According to Structural Engineer's Specifications & Design
- Conventional Steel Re-Enforced Slab w/ Bell Bottom Piers
- -- 3,000 PSI Concrete
- 6 mil. Polyethylene Vapor Barrier
- Termidor® or Equal Termite Pre-Treatment

Framing

- Roof, Wall and Floor Framing Designed and Inspected On-Site by Structural Engineer
- 2x4 or 2x6 Walls @ 16" On-Center Throughout According to Structural Engineer's Specifications & Design
- Treated Wood Baseplate on First Level
- Exterior Wall Bottom Plates Installed w/ Dow Weathermate® Sill Seal
- Ceiling Joist #2 SYP 16" On-Center, Size Per Structural Engineer's Specifications & Design
- 18" 24" Open Web Engineered Trusses for Floor Joist Framing at Second and Third Floors Size per Structural Engineer's Specifications
- Anthony Power Beams® or Equal for Structural Support Per Plan
- Subfloor 1-1/8" Tongue and Groove
 Advantech® or Equal
- Simpson® or Equal Hurricane Strapping

Building Envelope

- Building Envelope Inspected On-Site by Waterproofing & Roofing Consulting Engineer
- Engineered Wood Structural Sheathing, CDX, or Equal
- Commercial Grade **DuPont Tyvek®** or Equal for Exterior Building Wrap
- Dupont Tyvek® Tape, or Equal, and Grace Vycorner® or Equal Against Air & Water Penetration at Window Sills
- Dupont Tyvek® Tape, or Equal Seals Against Air
 & Water Penetration at Window & Door Jambs
- GAF StormGuard® Ice & Water Shield Used on the Underside of All Horizontal Over Hangs

Windows

- Sierra Pacific® or Equal Aluminum Clad Wood Windows
- Casement Style Operable Windows (Per Plan Location)
- Painted Wood Interiors
- Double-Paned Insulated Glass Thermally Broken
- Low E 366 Emulsion

Roofing

- 7/16" OSB Roof Decking
- 40 Year GAF Timberline® or Equal Composition Shingles w/30# Felt Underlayment
- Flat Roofs to be Torch Down Single Ply Bitumen Membrane
- Stainless Steel Flashing w/ Welded Corners
- Galvanized Drip Edge Flashing
- All Lead Roof Jacks Painted to Match Shingles

Exterior Materials (varies by plan and elevation)

- Clay Brick Exterior per Plan Locations
- Hand Carved Limestone Accents per Plan Locations
- James Hardie® Smooth Material for Fascia and Siding
- Tongue and Groove Solid Pine Soffit Materials at Porches (Painted)
- Custom Metal Balcony Railings and Window Boxes per Plan
- Sherwin-Williams® Exterior Latex Paint

Exterior Doors

- Custom Mahogany Entry Door
- Sierra Pacific® or Equal Aluminum Clad Wood Sliding Doors at CityRoom
- PlastPro® or Equal Fiberglass w/ Double Pane Low E Glass on All Other Exterior Doors w/ Endura FrameSaver® Jamb (Per Plan Location)
- Custom Fabricated Stainless Door Pans
- 26 Gauge Galvanized Head Flashing
- Compression Foam Weather-Stripping
- Black Aluminum Thresholds

Thermal Insulation

- Icynene® Open Cell ½ lbs Foam Insulation in All exterior walls, attic and all hot walls. (or equal)
- Icynene® or Equal Open Cell Sprayed-In Foam at All Sloped Ceilings or Inaccessible Areas
- Expandable Foam Polyseal at All Exterior Openings and Base Plates
- Dow Weathermate® Sill Seal at All 1st Floor Exterior Wall Bottom Plates



AS OF JUNE 1st, 2016

Garage

- Carriage Style Steel Insulated Overhead Door (Painted)
- 1 Automatic Garage Door Opener and Two Push Button Controls
- 2 2'x4' Fluorescent Lights
- 5/8" type "X" Fire —Code Sheetrock
- Base Boards (Paint Grade)
- Epoxy Floor Finish Selection Available, up to Tier 1, from Rohe & Wright's Design Studio

Drywall

- Gypsum Board Screw Applied
- 5/8" Throughout
- Rounded Corners Throughout
- Finish Level 4 on Walls & Ceilings
- Finish Texture Light Roll
- Mildew Resistant XP® or Equal Gypsum Board at Tubs and Shower Surrounds

MECHANICALS:

Heating & Air Conditioning

- Manual J & Manuel S Load per the Air Conditioning Contractors of America (ACCA) Calculated by Third Party Energy Engineer
- 16 SEER Dave Lennox® Condensing Unit(s)
 Zoned per Floor per the Manual J Load Calculation
- Honeywell® or Equal Touch Screen Thermostat(s)
- Lennox® MF-1 High Efficiency Pleated Air Filter(s)
- R-6 Insulated Duct Work with Mastic Sealed Joints
- All HVAC Units and Duct Work is Located in Conditioned Space

Elevator

- Residential Elevators Inc. or Equal Elevator
- 8' Tall Cab
- 4 Mini Lights in Cab
- Flooring to Match First Floor
- Hardwired Phone in Cab
- Cab Walls to be Custom Paneled and Stained
- Beveled Mirror on Back Wall

Fireplace

- Heatilator® or Equal 42" Metal Woodburning Fireplaces in Living Room
- Heatilator® or Equal 42" Direct Vent Gas
 Fireplace in City Room and Master Bedroom (Per
 Plan). Includes gas logs, glass panel, black trim and
 remote control.
- Up to Tier 3 Mantle Surrounds Selection Available from Rohe & Wright's Design Studio

Fire Protection

- 13 R (Single Dwelling) Professionally Designed and Installed Residential Fire Sprinkler System Throughout
- Xella® or Equal Fire Block Between Demising Walls of Attached Units.
- Draft Stopping and Fire Caulking

Electrical

- Extensive 5" Incandescent Recessed Can Lighting per plan
- Designer Lighting Fixture Selections available at Rohe & Wright's Design Studio to include Dining Room Chandelier (Tier 2), Island Pendants (Tier 2), Powder and Master Bath Vanity (Tier 3), Master Bath Hanging Chandelier, per plan, (Tier 2), 2nd Bath Vanity (Tier 2), Wall Sconces, per plan, (Tier 2)
- Choice of Designer Ceiling Fans in Bedrooms, Family Room, and City Room
- Gas & Electric Exterior Carriage Lights per Plan
- All Lighting Locations at Time of Rough-In Wiring to be Field Verified with Client
- Copper Branch Circuit Wiring Sizing Per Code
- Aluminum Underground Electrical Supply Wiring
- All Electrical Wall Outlets Installed in Baseboards (Except at Built-Ins)
- Structured Wiring Package Includes Alarm, Data, Phone and TV Wiring
- HAI or Equal Home Automation Customization, to include Additional Security and Lighting Available

Plumbing

- Navien® or Equal Tankless Water Heater w/ Recirculating System
- Uponor PEX® or Equal Water Supply Plumbed in a Trunk and Branch System
- Install Isolator Kits on Tankless Units.
- Gas Piped to Fireplace, Cook Top, Furnaces, Dryer, Tankless Water Heaters, Gas Lamps, and Gas Grill Location (Per Plan Location)
- Exterior Hose Bibs at Courtyard, Garage, and City Room Balcony
- Choice of Free-Standing Soaker Tub in Master Bath

Plumbing Fixture

- Kitchen Faucet Selection Available, up to Tier 4, from Rohe & Wright's Design Studio.
- Bar Faucet (per plan) Selection Available, up to Tier
 from Rohe & Wright's Design Studio
- Utility Room Faucet Selections Available, up to Tier
 1, from Rohe & Wright's Design Studio
- Master and Powder Bath Fixture Selections Available, up to Tier 3, from Rohe & Wright's Design Studio



AS OF JUNE 1st, 2016

- Secondary Bath Fixture Selections Available, up to Tier 3, from Rohe & Wright's Design Studio
- Free-Standing 66" Soaker Tub Selection Available, up to Tier 3, from Rohe & Wright's Design Studio
- Comfort-Height, Elongated Drake Toilet Available in Master & Powder (per plan)
- Elongated Toto Toilet Available in all Secondary Baths

FEATURES:

Appliances

- Thermador Professional Series, Commercial-Depth, 48" 6-Burner w/griddle, Dual-Fuel Gas Range.
- Thermador Masterpiece, Professional Series, 24" Microwave
- Thermador Emerald, Professional Series 4-Program Dishwasher
- Thermador Freedom Collection, Panel-Ready, 48-Inch, Dual Column Refrigerator/Freezer

Flooring

- Natural Stone or Porcelain Flooring, up to Tier 3, available for selection from Rohe & Wright's Design Studio in Foyer, Elevator, Bar, and Master Bath
- Natural Stone or Porcelain Flooring, up to Tier 1, available for selection from Rohe & Wright's Design Studio in Secondary Baths, and Utility Room
- Carpet Flooring selection at Tier 1 from Rohe & Wright's Design Studio in Master, Master His'/Her's Closet, Secondary Bedrooms and Closets
- Designer Hardwood Flooring Selection, up to Tier
 a available for selection from Rohe & Wright's
 Design Studio in Library (per plan), Powder Bath,
 Breakfast, Dining Room, Family Room, Game
 Room (per plan), Kitchen, Pantry, and Hallways.
- Stained Oak Stair Treads on All Stairs with Painted Risers and Skirt.
- Travertine Pavers, up to Tier 2 Selection from Rohe & Wright's Design Studio, on balconies, dry set over pedestals

Cabinets

- All Cabinets in Kitchen, Buffet/Butler's Pantry (per plan), Bar (per plan), Living Room Built-ins (per plan), and Powder Room to be Maple, Full-Overlay, Frameless, with a Tier 3 Door Style in either Thermofoil, Paint, Paint Highlight-Glazing, Stain, or Stain Highlight-Glazing
- All Cabinets in Master Bath and Master Suite (per plan) to be Maple, Full-Overlay, Frameless, with a Tier 2 Door Style in either Thermofoil, Paint, Stain, or Stain Highlight-Glazing
- All Cabinets in Secondary Baths and Utility (per plan) to be Maple, Full-Overlay, Frameless, with a Tier 2 Door Style in either Thermofoil or Stain

Self-Closing Drawer Glides and Door Hinges in all interior Locations

Countertops, Backsplash, & Tile Surrounds

- Kitchen, Master Bath, Powder Bath, and City Room (Per Plan) Countertop Selection Available, up to Tier 2, from Rohe & Wright's Design Studio. Tier 2 Selections include an assortment of Natural Stone, Granite, and Designer Quartz Selections.
- Kitchen Tile/Stone Backsplash Selections Available, up to Tier 5, from Rohe & Wright's Design Studio.
- Granite or Marble Slab Counter Tops at Secondary Bathrooms and Utility Room Selections Available, Tier 1, at Rohe & Wright's Design Studio. Includes 4" Backsplash
- Master Bath Tub and Shower Stone/Tile Surround Selection Available, up to Tier 3, from Rohe & Wright's Design Studio.
- Secondary Bath Tub/Shower Stone/Tile Surrounds Selection Available, up to Tier 1, from Rohe & Wright's Design Studio.

Hardware

- Bath Hardware Selections Available, up to Tier 2, from Rohe & Wright's Design Studio. One Towel Ring Per Vanity Locations
- Cabinet Hardware Selections Available for Kitchen, Buffet/Butler's Pantry (per plan), Bar (per plan), Living Room Built-ins (per plan), and Powder Room to, up to Tier 2, from Rohe & Wright's Design Studio
- Cabinet Hardware Selections Available for Secondary Baths and Utility (per plan) Tier 1, from Rohe & Wright's Design Studio
- Interior Door Hardware Selections Available up to Tier 2, from Rohe & Wright's Design Studio
- Front Door Handles Selections Available, up to Tier 4, from Rohe & Wright's Design Studio and will be approved by Town Arch.

Interior Doors & Trim

- 8'-0" Tall Painted Solid Core Painted Interior Doors in Choice of Style
- Two Piece 3-1/2" Casing on All Doors and Cased Openings, C-196 or C11 w/ Applied Bullnose Trim (Paint Grade)
- Two Piece Base Boards 12" MDF w/ PM-6 Moulding Entry, Second Floor, and Master Bedroom (Paint Grade)
- Two Piece Base Boards 8" MDF w/ PM-6 Moulding at Remaining Locations (Paint Grade)
- Duplex Crown Moulding Entry, Second Floor, and Master Bedroom, CM-48 w/ B-297 (Painted)
- Single Crown Moulding in All Remaining Areas Except Pantry, Garage, & Closets (Paint Grade)
- Window Stool 1-1/2" Half-Round Front w/ C196 Moulding
- Stain Grade block paneling and bookshelves in



AS OF JUNE 1st, 2016

- Library OR Study Per Plan for location of shelving (Mahogany or Alder or equal). Stain Grade Solid wood Doors to match species of wood chosen.
- All Master Closets to be Rod & Shelf with Field Field-Built Bulk-Head Cabinets/Benches (per plan) Painted

Glass and Mirrors (Per Allowance Addendum)

- Frameless 3/8" Style Glass Shower Enclosure in Master Bath (per plan)
- Semi-Frameless ¼" Style Glass Shower Enclosure in Secondary Bath Locations with Stand-up Shower (per plan)
- Framed Mirrors in Master Bath and Powder Bath per Selections Available at Rohe & Wright's Design Studio
- Floating Beveled Glass Mirror in all Secondary Bath Locations
- Glass Cabinet Doors per Plan. Glass Style Selections Available at Rohe & Wright's Design Studio.
- Beveled Mirror on Back Wall of Elevator

Drives and Walks

- 3-1/2" Thick 3,000 PSI Concrete
- #3 Re-Bar @ 15" O.C
- Cobblestone Pavers over the concrete on driveway
- 1"x4" Pressure Treated Expansion Joints

Landscaping & Irrigation

- Professionally Designed and Installed Landscaping
- Professionally Designed and Installed Irrigation System
- Underground Piped Drainage

Paint

Interior

- Sherwin Williams® Paints and Minwax® Stains
- Two Coats Flat Latex Paint on Ceilings (One Color)
- Two Coats Flat Latex on All Interior Walls (Three Colors Total)
- One Coat Primer on All Interior Trim and Cabinets
- Two Coats of Semi-Gloss Oil Based Enamel on Interior Trim (One Color)
- Light Rolled Texture on Walls and Ceilings
- Stain Grade Trim and Cabinets One Coat Stain w/ Two Coats Clear Sealer
 Exterior
- Sherwin Williams® Paints
- One Coat Primer w/ Two Coats Latex on All Painted Surfaces
- One Coat Masonry Primer w/ Two Coats Elastomeric Coating on Any Stucco Surfaces.
- Minwax® or Equal on Any Exterior Stained Wood

Stair Parts

- Stained Oak Stair Treads on All Stairs with Painted Risers and Skirt.
- Wrought Iron Stair Selection Available, up to Tier 1, from Rohe & Wright's Design Studio

ENERGY EFFICIENCY:

Qualification

- Röhe & Wright is a Certified Residential Energy Services Network (RESNET) Energy Smart Builder
- All Röhe & Wright Homes Adhere to the Home Energy Rating System (HERS)
- Each Home is Given a HERS Index Score to Rate Overall Energy Efficiency
- HERS Calculations, Inspections, and Scoring Performed by a Third Party Energy Engineer

Inspection

 Visual Inspections for Proper Installation of the HVAC System, Thermal Insulation, Windows, Exterior Doors, and Building Envelope are Performed On-Site Inspections by a Third Party Energy Engineer

Testing

- HVAC Duct Leakage Test
- Diagnostic Blower Door Test
- Tests Measure the Amount of Air Tightness
 Integrity of the Building Envelope, Air Tightness
 Integrity of the HVAC Distribution Ducts, and the
 Air Tightness Integrity and Effectiveness of
 Insulation Inside Walls and Ceilings

Building Products

- Dow Weathermate® Sill Seal at All 1st Floor Exterior Wall Bottom Plates
- Icynene® Open Cell ½ lbs Foam Insulation in All exterior walls, attic and all hot walls. (or equal)
- ZIP System® or Equal Structural and Waterproofing system for Building Wrap
- Windows & Exterior Doors Industry Leading SHGC & U-Factor Ratings
- Windows Use Thermally Broken Construction w/ Double Pane Low E Glass Emulsion
- Exterior Doors Have Double Pane Low E Glass
 Emulsion (Per Plans Location)
- 16 SEER Dave Lennox® Condensing Unit(s)
 Zoned for Greatest Efficiency
- R-6 Rated HVAC Distribution Duct
- All HVAC Units and Ducts Installed in Conditioned Space
- Honeywell® or Equal Touch Screen Programmable Thermostat(s)
- High Efficiency Natural Gas Navien® Tankless Water Heater(s)