



# Insulation Certificate

This form must be filled out and posted to comply with building code requirements. Meets IRC Sections N1101.3, N1101.41, and N1101.8 requirements.

The following spray polyurethane foam product(s) has/have been installed.

- FOAM-LOK™ OC-Open Cell Spray Foam Insulation
- FOAM-LOK™ CC-Closed Cell Spray Foam Insulation
- FOAM-LOK™ CW-Closed Cell for Cold Weather Spray Polyurethane Foam

Consult International Building Code, Chapter 26-Plastic and International Residential Code (IRC) R314 Foam Plastics for specific requirements. The spray polyurethane foam insulation system(s) has/have been installed in accordance with manufacturer's processing guidelines to provide a thermal resistance of:

Area Insulated	Aged R-Value	Thickness**
Attic Area	R- <b>28</b>	At <b>5.5 to 6</b> inches
Sloped Ceilings	R-	At inches
Walls (Location: Exterior )	R- <b>16</b>	At 3.5 inches
Walls (Location: )	R-	At inches
Floors (over an unheated crawl space)	R-	At inches
Crawl Space Perimeter	R-	At inches
Basement Exterior Walls	R-	At inches
Other (Location: )	R-	At inches

\*\* Nominal thicknesses are representative of field, spray-applied foam material

Jobsite Address: 910 W 31st Street

Date of Installation: **9/05/19**

Building Contractor: Arturo

FOAM-LOK Contractor: **Dr. Foam Insulation** Phone: **(832) 944-0002**

Installed By: Ivan Rodriguez / Sam Ortega

-Post Near Electrical Panel-

