


18	
6	GENERAL NOTES
SD	SMOKE DETECTORS are required in all dwellings units and must be instulied in accordance with the International Building Code. These detectors must receive their primary power via direct wiring into the house current and be equipped with a battery back-up & interconnected.
V	In each utility room and bathroom, a window must be openable or a mechanical vent is required.
w	IN EVERY BEDROOM, a window must be openable NET CLEAR OPENING WIDTH IS 20 INCHES NET CLEAR OPENING HEGHT IS 24 INCHES NET CLEAR OPENING HEGHT IS 24 INCHES NET CLEAR OPENINGLE AREA IS 3.7 SQ. FT. 2ND FLOOR NET CLEAR OPENINGLE AREA IS 3.7 SQ. FT. 2ND FLOOR
(HB)	VACUUM BREAKERS REQUIRED ON ALL HOSE BIBS AS PER THE INTERNATIONAL PLUMBING CODE.
(W/H)	Pilot light must be 18 inches above finish floor
FULL DWN STAIRS	Heating unit installed in attic may not be more than 20 feet from attic access.
NOTE:	240-24 LOCATION IN OR ON PREMISES (d) Not in vacinity of acality ignitible material. Overcurrent devices shall not be located in the vicinity of easily ignitable material such as clothes closets.
GARAGE	Required association between the residence and gaptage musi-cosist of one-half $(1/2)$ linch grpaum board installed on the garage side and o tight fifting, weather-stipped solid core wood door at least one and three-sight $(1-5/4)$ inches in histories at any point. A labeled fire and the time is used in lieu of the solid core door.
GLASS	Regulations for interior and exterior window and door safety glazing are set forth by IRC 2006 R308.4

NOTE:

Any specific additional items not called out on on this plan that are desired is as per owner! Builder to verify!



NOTE:

Location of beams subject to change as per framer.

NOTE:

Foundation, framing package, & windstorm by other.

	AREAS		٦
	LIVING	1,992 SQ. FT.	_
	AUTO STORAGE	456 SQ. FT.	
	COVERED PORCH	35 SQ. FT.	
	COVERED PATIO	304 SQ. FT.	
Ļ	TOTAL UNDER ROOF	2,787 SQ. FT.	_ _

Copyright©	This pican is for construction of one building only and is not to be copied in anyway without the written permission from Freeman Custom Home Design.	NOTE:	tuestions concerning initial ayour or traming should be directed to Freeman Custom Home Design.	Freeman Custom Home Designs is not responsible for	framing discrepancies that deviate from this plan, if not colled before completely framed. See Above	
REVISIONS						
Freeman Custom Home Design assumes no liability	Before construction, the purchaser, builder or contractor must varify all	dimensions, verify compliance with all huilding codes and incommende site	conditions. Only a qualified designer,	architect, or structural engineer should	be permitted to alter these plans,	
	A New Home by:	Manley Homes		0102 Anno Ct	JION WIIIIA JI	
DRA	A NEW HOILE BY:	Hard Manley Homes	T EFREEMAN_CUUSTOM		Tony freeman, Owner (832)/39-4142	