


GENERAL NOTES

- 10'-0" CEILING HEIGHTS AT FIRST FLOOR (U.O.N)
- 9'-0" CEILING HEIGHTS AT SECOND FLOOR (U.O.N)
- ALL EXTERIOR WALLS TO BE 2X6 @ 16 O.C.
- CARPET FLOORS (U.O.N)
- RAM INDUSTRIES HEAVY FRAME BRONZE TINTED ALUMINUM CASSETTE WINDOWS, AT 8'-0" HEAD HT. @ FIRST FLOOR, 7'-0" @ SECOND FLOOR (U.O.N)
- 1-3/8" 2-PANEL INTERIOR DOORS. 8'-0" AT FIRST FLOOR, 7'-0" AT SECOND FLOOR (U.O.N)
- 1-3/4" SOLID CORE EXTERIOR DOORS.
- MECHANICAL ACCESSORIES ARE PROVIDED ON PLAN TO SERVICE MECHANICAL EQUIPMENT ONLY. THE ROUGH OPENING SHALL BE 30" X 54" AND THE STAIR LOAD CAPACITY SHALL BE A MIN. OF 350 POUND CAPACITY. PER IRC M1605.13

BATH SCHEDULE

- TILE FLOORS (U.O.N)
- TILE WALLS AT TUB ALCOVES TO CEILING.
- TILE FULL AT SHOWERS.
- SLAB STONE DRAIN AND SPLASH (U.O.N)

ARCHITECTURAL SOLUTIONS, INC.



1616 S. Voss, Suite 85C
Houston, Texas 77057
Phone: (713)978-6985
Fax: (713)978-7085



A Custom Residence
MARTHA AND JIM KAHLDEN
PARKER BUILDERS, INC.

4051 Underwood Blvd.
Houston, Texas 77025

PROJECT NUMBER	080401
PLAN NUMBER	3576
DATE	CHECKED
REV/DATE	DATE
AREA TABULATION	

FIRST FLOOR	2
SECOND FLOOR	1
TOTAL LIVING AREA	3
2 CAR GARAGE	
APRON	
COVERED PORCH AND PATIO	
BALCONIES	
TOTAL COVERED AREA	4

FIRST FLOOR PLAN

SCALE 1/4" = 1'-0"
DATE: June 27, 2008

A1.10

Architectural Solutions Inc. 3008