ENERGY STAR® Certified in All 50 States









Exterior Door Insulated Fiberglass Wood Edge Door THC-M-5*

ENERGY PERFORMANCE RATINGS

Product Description** Wood/Composite Frame	U-Factor¹/Solar Heat Gain Coefficient (SHGC) Individual Option Number			
	1/2" IG	0.20 / 0.09	0.25 / 0.17	0.29 / 0.23
02866-00001		02950-00001	03034-00001	rack Fablus
5/6" IG	0.20 / 0.09	0.25 / 0.17	0.28 / 0.23	
	02869-00001	02953-00001	03037-00001	
5/8" IG with Internal Dividers	0.20 / 0.08	0.25 / 0.15	0.29 / 0.20	
	02870-00001	02954-00001	03038-00001	
5/8" IG Triple Pane	0.19 / 0.08	0.24 / 0.15	0.27 / 0.20	
	02949-00001	03033-00001	03117-00001	
3/4" IG	0.20 / 0.09	0.24 / 0.17	0.27 / 0.23	
	02872-00001	02956-00001	03040-00001	
3/4" IG with Internal Dividers	0.20 / 0.08	0.25 / 0.15	0.28 / 0.20	
	02873-00001	02957-00001	03041-00001	
3/4" IG Triple Pane	0.19 / 0.08	0.22 / 0.15	0.25 / 0.20	
	02874-00001	02958-00001	03042-00001	
1" IG	0.20 / 0.09	0.24 / 0.17	0.28 / 0.23	
	02875-00001	02959-00001	03043-00001	
1" IG with Internal Dividers	0.20 / 0.08	0.24 / 0.15	0.28 / 0.20	
	02875-00002	02959-00002	03043-00002	Series Series
1" IG with Internal Wrought Iron Dividers	0.20 / 0.08	0.25 0.15	0.28 / 0.20	
	02877-00001	02961-00001	03045-00001	
1" IG with Miniblinds	0.21 / 0.07		0.30 / 0.18	
	02878-00001		03046-00001	
	, u U8	0.21 / 0.15	0.23 / 0.20	
			00001-00001	131 90

THERMA TRU® Durable Doorlite Frame No warping DOORS

· Can be painted or stained a dark color

• Can be used behind a storm door

TO REMOVE GLAZING COMPOUND: Wet with window cleaner or water first. Use razor blade to score glazing along edge of frame. Holding razor blade at 45° angle, scrape glazing from glass. Wipe remaining residue off with window cleaner or mineral spirits. FINISH FRAME WITHIN SIX MONTHS OF EXPOSURE.

TO FINISH THE FRAME AROUND GLASS: Clean first with mild detergent and water or TSP solution. Rinse well and allow to dry.

PAINT: Prime first with an alkyd- or acrylic-based primer and allow to dry. Then paint with a high quality, exterior grade, acrylic-latex house paint, OR,

STAIN AND TOPCOAT: Use a Therma-Tru Finishing System Kit only. To order a Therma-Tru Finishing System Kit, contact your local Therma-Tru dealer, visit us on the Internet at www. thermatru.com or call toll free at 1-877-99-STAIN (997-8246). See the Finishing System Instruction brochure or the Corner Door Tag for more detailed application information.

CAUTION: Complete curing of the finish over a polymer part generally requires a longer period of time than on other surfaces.

DECORATIVE GLASS: Our Therma-Tru artisans have hand-crafted the decorative glass in this door system, and as with any hand-crafted product, no two are alike. Slight irregularities and imperfections should not be considered defects.

WARRANTY INFORMATION: This product is covered by a limited warranty. The warranty does not cover defects that are the result of finishing or installation not in accordance with our instructions. For further information contact:

THERMA-TRU DOORS • Technical Services Department
P.O. Box 8780 • Maumee, Ohio 43537 • 1-800-THERMATRU (843-7628) • www.thermatru.com

4/5/02 DLLB₁*U