

## **NOTES ON INSTALLATION**

**Follow manufacturer's installation instructions.** Complete installation instructions should be accessed at **ntwindow.com/installation**.

Always ensure that replacement windows are of the correct type and size prior to removal of existing windows.

Windows must be properly shimmed and installed plumb, level & square and must be properly sealed against air and water infiltration.



Safety Warning: Do not leave small children and or pets unattended when windows are open or unlocked; screens are not designed as safety constraints. Further window and door safety tips can be found at **ntwindow.com/windowsafety**.

Find us:

MP0040 07/18



(











National Fenestration Rating Gouncil®

#### NT Window Inc

NTW-A-6-00207-00001

T150 - TWINSULATOR SH PW DUAL GLAZED - ARGON FILL - LOWE 366

ALUMINUM THERMALLY IMPROVED

#### **ENERGY PERFORMANCE RATINGS**

U-Factor (U.S./I-P)

Solar Heat Gain Coefficient

0.33

0.25

### **ADDITIONAL PERFORMANCE RATINGS**

Visible Transmittance


Air Leakage (U.S./I-P)

0.58

 $\leq 0.3$ 

Minufacturer stibulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult Manufacturer's literature for other product performance information www.nfrc.org

ORDER: 435280 - 10 S:74646 B:1 BIN:6





# We'd love to see this window installed.

Please take a moment to send us a photo of your final installation and we'll send you a \$25 Visa Gift Card. Visit **ntwindow.com/myphotos** for more information or simply scan the QR code:

