ELEVATION CERTIFICATE

O.M.B. No. Suor-Ware Expires July 31, 1999

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions for completing this form can be found on the following pages.

		FOR INSURANCE COMPANY USE					
BUILDING OWNER'S NAME		POLICY NUMBER					
STREET ADDRESS (Including Apt. 338 A DM'I P. OTHER DESCRIPTION (Lot and B	COMPANY MAIC NUMBER						
TIKI ISLAH	STATE TX	ZIP CODE					
SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION							
Provide the following from the proper FIRM (See Instructions):							
1.00mmunity number 485470	2. PANEL NUMBER 0241	s. Buffix	4. DATE OF FIRM INDEX 5/02/83	s. FIRM ZONE V 2.0	e. BASE FLOCO ELEVATION (IN AO Zones, use disph)		
7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): SINGVD '29 Other (describe on back) 8. For Zongs A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: Literal Literal NGVD (or other FIRM datum-see Section B, Item 7).							
	SECTK	ON C BUILDI	ng Elevation inform	MOTA			
2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of Line 1 leet NGVD (or other FIRM datum-see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of Line 1 leet NGVD (or other FIRM datum-see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is Line 1 leet above or below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is Line building's lowest floor (reference level) alevated in accordance with the community's floodplain management ordinance? NGVD 129 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: X ves No (See Instructions on Page 4)							
5. The reference level elevation is based on: A school construction in construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)							
5. The elevation of the lowest grade immediately adjacent to the building is: 1. 1. 5. 2. feet NGVD (or other FIRM datum-see Section 8, Item 7).							
SECTION D COMMUNITY INFORMATION							
if the community official re is not the "lowest floor" as floor" as defined by the or 2. Date of the start of constr	s defined in the commodinance is:	munity's floodp	ieln management ordinari NGVD (or other FIRM dat	ce, the elevation um-see Section	ndicated in Section C, item 1 of the building's "lowest 8, item 7).		

SECTION E CERTIFICATION

This cartification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE), V1-V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 5, 7 and 6 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by line or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME				
CHRISTOPHER	RUSKY COMPANY MAINE	JMBER (or Affix Seat)		
PATLE	COMPANY NAME	5247		
ADDRESS	THE -AND	SURVEY (20.	
2222 CEDAG TO	CITY	•	STATE	2;P
SIGNATURE	SA MAR	QUE	_TX	77568
Conica about	6/2	2 100	LIAO AS	8-1041
Copies should be made of the Certificate for	: 1) community official, 2) insura	nce agent/company,	and 3) building	gwner.
				Anna
COMMENTS:			-	

				~~~
				<del></del>
	-	·	<del></del>	
On On				
BLAB	with Basement		PILES, R COLUMNS .	
A V ZONES ZONES	. A	A	v	
44.04	ZONES	ZONES	ZONES THE	
मारकिटरी		ALCEPTURE TO		ENCICE
	PLOOD ELEVATION	, 17		1874
Extrasion to March			J	~~
PASE VLOCO	ADJACENT GRACE LEVEL		' M -	MASE .
ACTURACE ACTURACE ACTURACE	and Livis	<b>M</b> :	[ <b>1</b> €	AASE LGCO LVATED
			W	j
		Ŋ	<b>19</b>	CACENT .
		# <i>(</i> 1)	· 1861 - 4	200

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member