



This home has been professionally insulated with

# Owens Corning PROPINK® L77 PINK Fiberglas™ Unbonded Loosefill Insulation

(Job Site Address)

Name \_\_\_\_\_  
 Address 1103 Baffin Ln  
 City Houston State Tx Zip 77090

## Owens Corning™ PROPINK® L77 PINK Fiberglas™ Unbonded Loosefill Insulation

Owens Corning will accept no responsibility when the product is not installed in accordance with the product label. Stated R-value is provided by installing the required number of bags at a thickness not less than the labeled minimum thickness. Installation of the required number of bags may yield more than the specified minimum thickness. Failure by the installer to provide both the required bags and at least the minimum thickness will result in lower insulation R-value.

### Specification for Open Blow Attics

New Construction  Retrofit

Number of bags used 28

Estimated R-value of previous insulation \_\_\_\_\_

Area of coverage (sq. ft.) 2152

Other type(s) of insulation in attic \_\_\_\_\_

Thickness of insulation \_\_\_\_\_

Depth of previous insulation \_\_\_\_\_

### Attics

R-value	Bags Per 1000 Sq.Ft.	Maximum Net Coverage	Minimum Weight/ Sq. Ft.	Minimum Thickness (in)	Minimum Settled Thickness <sup>1</sup>
R-13	5.5	182.9	0.180	4.75	4.75
R-19	8.1	124.2	0.266	6.75	6.75
R-22	9.4	106.3	0.311	7.75	7.75
R-26	11.2	89.6	0.368	9.00	9.00
<b>R-30</b>	13.0	77.0	0.428	<b>10.25</b>	10.25
R-38	16.8	59.5	0.555	12.75	12.75
R-44	20.1	49.8	0.662	14.75	14.75
R-49	22.6	44.2	0.747	16.25	16.25
R-60	28.5	35.1	0.940	19.50	19.50

### Walls

R-value	Minimum Thickness	Installed Density Lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1000 Sq. Ft.	Minimum weight Lbs. Per Sq. Ft.
13	3.5 (2x4)	1.3	87.0	11.5	0.379
15	3.5 (2x4)	1.5	75.4	13.3	0.438
21	5.5 (2x6)	1.3	55.4	18.1	0.596
24	5.5 (2x6)	1.8	40.0	25.0	0.825

### Floors

R-value	Minimum Thickness	Installed Density Lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1000 Sq. Ft.	Minimum weight Lbs. Per Sq. Ft.
31	2x8	1.4	39.0	25.6	0.846
39	2x10	1.4	30.6	32.7	1.079
48	2x12	1.5	23.5	42.6	1.406

### Cathedral Ceiling

R-value	Minimum Thickness	Installed Density Lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1000 Sq. Ft.	Minimum weight Lbs. Per Sq. Ft.
28	2x8	1.3	42.0	23.8	0.785
36	2x10	1.3	32.9	30.4	1.002
44	2x12	1.3	27.1	36.9	1.219

<sup>1</sup>This product shows negligible settling.

Loosefill insulations vary in thermal performance due to factors such as aging, mean temperature, settlement, convection, moisture absorption and installation variation. Convection in glass loosefill insulation installed in open attics can reduce its thermal performance in extreme winter temperatures during the heating season.

Contractor Installed Building Products-Houston Date 06/30/2021 Builder \_\_\_\_\_ Date \_\_\_\_\_

Company Sarah Falcon Company \_\_\_\_\_  
(Signature) (Signature)

Address 16526 Air Center Blvd. Houston, TX 77032 Address \_\_\_\_\_

Phone 281-875-1100 Phone \_\_\_\_\_

**OWENS CORNING INSULATING SYSTEMS, LLC**  
 ONE OWENS CORNING PARKWAY  
 TOLEDO, OHIO, USA 43659  
**1-800-GET-PINK®**  
[www.owenscorning.com](http://www.owenscorning.com)



Pub. No. 10012954. Printed in U.S.A. September 2010.  
The color PINK is a registered trademark of Owens Corning.  
©2010 Owens Corning.