



SHOWER NOTES:
 TILE FLOOR IN SHOWER AND RESTROOM TO BE FLUSH. SHOWER FLOOR SLOPES TO DRAIN. GLASS SHOWER DOOR AND GLASS PANE TO BE TEMPERED. SHOWER TO HAVE SINGLE LEVER WATER CONTROL. SHOWER HEAD AT 6'-4" AFF. SHOWER ENCLOSURE TO BE FULLY TILED FROM FLOOR TO CEILING. SHOWER CEILING TO BE WATER RESISTANT GWD PAINTED WITH KILZ (OR EQUAL) MOLD RESISTANT PAINT. USE CEMENT BACKER BOARD FOR ALL TILE SURFACES. USE INTEGRATED SHOWER WATERPROOFING SYSTEM BY SCHLUTER (OR EQUAL) INCLUDING WATERPROOFING MEMBRANE, CORNER SEALS, AND DRAIN KIT PER MANUFACTURER INSTRUCTIONS. SHOWER WATERPROOFING SYSTEM TO BE WATER TESTED PRIOR TO COVERING.

NOTE TO ELECTRICIAN:
 INTERIOR WALLS ON SECOND AND THIRD FLOOR HAVE TWO LAYERS OF 1/2" GWB FOR ACOUSTICAL INSULATION. SPECIAL ELECTRICAL SWITCH AND OUTLET ROUGH-IN BOXES MAY BE REQUIRED TO ACCOMMODATE GWD THICKNESS. CONSULT WITH OWNER AND CONTRACTOR ON OTHER RELATED REQUIREMENTS.



03 THIRD FLOOR PLAN
 SCALE: 1/4" = 1'-0"

NORTH