



PRODUCT NO. F84CNP060L00EJAA
MODEL NO. F84CNP060
SERIAL NO. 4121F11423
VOLTS 208/230
MOTOR HP 3/4
MOTOR FLA 6
PHASE/HERTZ 1/60
TEST STATIC 0.2 IN. W.C.
REFRIGERANT 410A DESIGN PSIG 450
DATE OF MANUFACTURE OCT 2021 4121F11423



F84CNP060L00EJAA



4121F11423

Approved Electric Heater Accessories

KFCEH**01N05*	KFCEH**01C05*	KFCEH**01N08*	KFCEH**01C08*
KFCEH**01N09*	KFCEH**01N10*	KFCEH**01C10*	KFCEH**01F15*
KFCEH**01C15*	KFCEH**01S15*	KFCEH**01S18*	KFCEH**01F20*
KFCEH**01C20*	KFCEH**01F24*	KFCEH**01F30*	** - NUMERIC

ELECTRICAL INFORMATION FOR THIS UNIT
 FOR FIELD INSTALLED ELECTRIC HEATERS APPLY ELECTRICAL INFORMATION
 PLATE SUPPLIED WITH HEATER IN THIS BLOCK.

SINGLE SUPPLY CIRCUIT

L1/L2 HEATER AMPS 0	MIN. AMPACITY 7.5
MAX. OVERCUR. PROTECTION 15	

DUAL SUPPLY CIRCUIT

L1/L2 HEATER AMPS N/A	MIN. AMPACITY N/A
MAX. OVERCUR. PROTECTION N/A	
L3/L4 HEATER AMPS N/A	MIN. AMPACITY N/A
MAX. OVERCUR. PROTECTION N/A	

HEAT PACK INSTALLED N/A


SHORT CIRCUIT CURRENT: 5KA RMS
 SYMMETRICAL, 230 V

UNIT HAS INTEGRAL LIMIT CONTROL, MAX. OUTLET TEMP. 230F
 MOTOR ELECTRONICALLY PROTECTED.
 SEE INSTALLATION INSTRUCTIONS FOR SPECIFIC INSTALLATION REQUIREMENTS AND
 APPROVED ACCESSORY KIT INFORMATION.
 MAX. VOLTAGE TO GROUND OF SUPPLY CIRCUIT NOT TO EXCEED 120 VOLTS IF HEATER
 HAS CIRCUIT BREAKER CONTROL.
 COIL FOR COOLING ONLY EXCEPT WHEN INSTALLED AS PART OF A LISTED HEAT PUMP.
 USE ONLY ACCESSORY ELECTRIC HEATERS SHOWN IN "APPROVED ACCESSORIES"
 SECTION AND FROM EQUIPMENT MANUFACTURER.
 CLEARANCE TO COMBUSTIBLE MATERIALS TO BE 4" FOR CASING, PLENUM AND DUCT FOR
 UNITS WITH 0 TO 18KW HEATERS.
 FOR UNITS WITH HEATERS 20KW AND ABOVE, CLEARANCE TO COMBUSTIBLE MATERIAL IS
 TO BE 0" TO CASING AND 1" FOR FIRST 36" OF PLENUM AND DUCT.


CAUTION METERING DEVICE FOR THIS COIL MUST
 MATCH THAT SHOWN ON OUTDOOR UNIT
 RATING PLATE. REPLACE IF NECESSARY.
 THIS UNIT IS EQUIPPED WITH METERING DEVICE.

TXV

CAC/BDP
 7310 W. Morris Street
 Indianapolis, IN 46231 U.S.A.
 342557-4770
 ENGINEERED IN USA
 ASSEMBLED IN MEXICO



SERIAL NUMBER
3621E17684
PRODUCT NUMBER
 24ABC660B0031011
MODEL NUMBER
 24ABC660B310






METERING DEVICE TXV INDOOR NA OUTDOOR
FACTORY CHARGED 14.00 LBS R410A
INDOOR TXV SUB COOLING 6.35 KG
POWER SUPPLY 208-230 VOLTS AC
 PH 60 HZ
PERMISSIBLE VOLTAGE AT UNIT
 MAX 253 MIN 197

SUITABLE FOR OUTDOOR USE

COMPRESSOR	208/230 VOLTS AC
1 PH	60 HZ
23.7 RLA	152.5 LRA

FAN MOTOR	208/230 VOLTS AC
1 PH	60 HZ
1/3 HP	2.80 FLR

DESIGN/TEST PRESSURE GAGE
 HI 450 PSI 3103 KPA
 LO 250 PSI 1724 KPA
MAX DESIGN/WORKING PRESSURE
 700 PSIG 4826 KPA
MINIMUM CIRCUIT AMPS 32.4
MAX FUSE 50 A **MAX CKT-BKR** 50 A
Short Circuit Current 5KA rms, symmetrical, 230V
DATE OF MANUFACTURE SEP 2021

AHRI CERTIFIED
 AHRI Standard 210/240
 Performance ratings are based on the complete
 system in which used.

Carrier Corporation
 7310 W. Morris Street
 Indianapolis, IN 46231
 33866-4007

Installation Prohibited in Southwest

