

THIS SURVEY DOES NOT ADDRESS ANY EAVES, GUTTERS OR OTHER OVERHANGING STRUCTURE FEATURES, WHICH MAY PROTRUDE OVER BOUNDARY, EASEMENT AND/OR BUILDING LINES, UNLESS OTHERWISE SHOWN HEREON.

(#) THE TOP OF ALL FLOOR SLABS SHALL BE A MINIMUM OF 84,50 FEET ABOVE SEA LEVEL. IN ADDITION TO THIS MINIMUM, NO FLOOR SLAB SHALL BE LESS THAN 1,5 FEET ABOVE NATURAL GROUND PER RECORDED PLAT NOTE #7.

REASON

FINAL ADD BUYER NAME

REVISIONS

DATE

TRI-TECH JOB NO: Y28302-17

FIELD DATE: 03-29-17
FLOOD INFORMATION

F.I.R.M. NO: <u>48157C</u> REVISED DATE: <u>04-02-14</u>

BEARING BASE: REFERRED TO PLAT NORTH

FLOOD INFORMATION PROVIDED HEREON IS BASED ON SCALING THE LOCATION OF THE SUBJECT TRACT ON THE FLOOD INSURANCE RATE MAPS, THE INFORMATION SHOULD BE USED TO DETERMINE FLOOD INSURANCE RATES ONLY AND IS NOT INTENDED TO IDENTIFY SPECIFIC FLOODING CONDITIONS. WE ARE NOT RESPONSIBLE FOR THE FJ.R.M.'S ACCURACY,

PANEL: 0235L ZONE: "X-SHADED"

CLIENT JOB NO: N/A
DRAWN BY: RSR

MARK S. BROWN

5553

SUFN

SURVEYOR REGISTRATION