

FIELD NOTES DESCRIPTION

OF A

34.02 ACRE TRACT

LEWIS COX LEAGUE SURVEY, ABSTRACT 13
PLEASANT GRAY LEAGUE SURVEY, ABSTRACT 24
HUNTSVILLE, WALKER COUNTY, TEXAS

A FIELD NOTES DESCRIPTION OF 34.02 ACRES IN THE LEWIS COX LEAGUE SURVEY, ABSTRACT 13 AND PLEASANT GRAY LEAGUE SURVEY, ABSTRACT 24, IN HUNTSVILLE, WALKER COUNTY, TEXAS, BEING A PORTION OF THE REMAINDER OF A CALLED 248.20 ACRE TRACT OF LAND DESCRIBED IN A DEED TO SAM C. DOMINEY, RECORDED IN VOLUME 90, PAGE 488 OF THE DEED RECORDS OF WALKER COUNTY, TEXAS (DRWCT); SAID 34.02 ACRES BEING MORE PARTICULARLY DESCRIBED BY METES AND BOUNDS AS FOLLOWS:

BEGINNING at a 5/8 inch iron rod with a plastic cap stamped "RODS SURVEYING INC" found on the east line of Veterans Memorial Parkway (variable width right-of-way, 403/867 DRWCT) and being on the southeast line of said remainder of 248.20 acres, for the west corner of a portion of the remainder of a called 1,129.73 acre tract of land described in a deed to Robinson-Gibbs I, LLC recorded in Document No. 2019-51872 of the Official Records of Walker County, Texas (DRWCT) and being the south corner hereof;

THENCE, with the east line of Veterans Memorial Parkway for the following four (4) courses and distances:

- 1) N 37° 03' 17" W, for a distance of 398.06 feet to a 1/2 inch iron rod with a blue plastic cap stamped "KERR SURVEYING" set;
- 2) N 34° 14' 56° W, for a distance of 1,020.70 feet to a 5/8 inch iron rod with a plastic cap stamped "RODS SURVEYING INC" found:
- 3) with a curve to the right, having a radius of 3,950.21 feet, an arc length of 152.42 feet, a delta angle of 02° 12' 39", and a chord which bears N 33° 08' 16" W, a distance of 152.41 feet, to a 5/8 inch iron rod with a plastic cap stamped "RODS SURVEYING INC" found;
- 4) N 25° 38' 20° W, for a distance of 547.74 feet to a 5/8 inch iron rod with a plastic cap stamped "RODS SURVEYING INC" found on the south line of Smither Drive (variable width right-of-way, 403/867 DRWCT) for the northwest corner hereof;

THENCE. with south line of Smither Drive for the following three (3) courses and distances:

- 1) N 83° 15' 14" E. for a distance of 182.02 feet to a 1/2 inch iron rod with a blue plastic cap stamped "KERR SURVEYING" set;
- 2) 5 87° 53' 25" E, for a distance of 194.51 feet to a 1/2 inch iron rod with a blue plastic cap stamped "KERR SURVEYING" set;
- 3) 5 83° 27' 20° E, for a distance of 661.78 feet to a 1/2 inch iron rod with a blue plastic cap stamped "KERR SURVEYING" set for the northwest corner of a called 0.488 acre tract of land described in a deed to The City of Huntsville, recorded in Volume 403, Page 867 (DRWCT) and being a northeasterly corner hereof;

THENCE, with the established line of said 0.488 acres for the following three courses and distances:

- 1) 5 11° 35′ 01° W, for a distance of 191.24 feet to a 1/2 inch iron rod with a blue plastic cap stamped "KERR SURVEYING" set;
- 2) N 90° 00' 00" E, for a distance of 127.91 feet to a 1/2 inch iron rod with a blue plastic cap stamped "KERR SURVEYING" set;

3) N 19° 05' 03" E, for a distance of 83.70 feet to a right-of-way monument found on a westerly line of said portion of the remainder of 1,129.73 acres and being on the east line of the remainder of said 248.20 acres and being a northeasterly corner hereof;

THENCE, with the common line of said portion of the remainder of 1,129.73 acres and said remainder of 248.20 acres for the following two (2) courses and distances:

- 1) 5 25° 37' 22" E, for a distance of 1,167.56 feet to a 5/8 inch iron rod found for the west corner of said remainder of 248.20 acres and the west corner hereof;
- 2) 5 42° 50' 02" W, for a distance of 764.50 feet to the POINT OF BEGINNING hereof and containing 34.02 acres, more or less.

Surveyed on the ground June 2023 under my supervision. See plat prepared June 2023 for other information. The bearing basis for this survey is based on the Texas State Plane Coordinate System of 1983 (NAD83), Central Zone, Grid North as established from GPS observation using the Leica Smartnet NAD83 (NA2011) Epoch 2010 Multi-year CORS Solution 2 (MYCS2). Distances described herein are surface distances. To obtain grid distances (not grid areas) divide by a combined scale factor of 1.00012141700982 (calculated using GEOID12B). Reference drawing: 23-431-BOUNDARY5.

Nathan Paul Kerr

Registered Professional Land Surveyor No. 6834



Kerr Surveying, LLC | 409 N. Texas Ave. Bryan, TX 77803

Office: (979) 268-3195 | Web: www.kerrlandsurveying.com

Surveys@kerrsurveying.net | TBPELS Firm No. 10018500

