

ENERGY CONSERVATION

A202

GENERAL NOTES

RIM ELEVATION.

26. CONTRACTOR TO PROVIDE UNDERCOUNTER & ISLAND MILLWORK

27. CONTRACTOR TO COORDINATE ELECTRICAL REQUIREMENTS FOR

ICE MACHINE, WINE STORAGE, DISPOSAL, ETC.

28. CONTRACTOR TO VENT DRYER OUTSIDE.

ELECTRICAL FOR EQUIPMENT. I.E. DISHWASHER, REFRIGERATOR,

SMOKE DETECTORS SHALL BE HARD-WIRED, INTER-CONNECTED

CONTRACTOR SHALL INSTALL NECESSARY WOOD BLOCKING IN

STUD WALLS AS REQUIRED TO BACKUP WALL MOUNTED ITEMS.

. ALL WINDOWS TO BE CENTERED ON WALLS UNLESS OTHERWISE

ALL ANGLE WALLS TO BE ON A 45 DEGREE ANGLE UNLESS

AND WITH BATTERY BACK UP AS PER THE IRC R317.1.

OTHERWISE NOTED.

BE SOLID WOOD DOORS NOT LESS THAN 1-3/8 INCHES (35 MM) IN

THAN 13 /8 INCHES (35 MM) THICK, OR 20-MINUTE FIRE-RATED

40. THE FINISH FLOOR SHALL BE 12" ABOVE THE NEAREST MANHOLE

DOORS, EQUIPPED WITH A SELF-CLOSING DEVICE.

THICKNESS, SOLID OR HONEYCOMB- CORE STEEL DOORS NOT LESS