

### DOOR SCHEDULE

Type Mark	DESCRIPTION
37	TWIN 2'-0" X 8'-0" HOLLOW CORE
103	3 x 8 EXTERIOR
162	DOOR - MODERN TWIN SLIDER
172	3'-0" X 8'-0"
181	2'-4" X 8'-0"
193	3'-0" X 8'-0" FIRE RATED
198	3'-0" OPENING VERIFY HEIGHT & TYPE
213	2'-4" X 8'-0" POCKET DOOR
214	3'-0" X 8'-0" POCKET DOOR
273	2'-4" X 8'-0" TEMPERED GLASS SHOWER DOOR
291	18'-0" X 8'-0" OVERHEAD DOOR
300	4'-0" X 8'-0" MODERN TWIN
301	9'-0" X 8'-0" OVERHEAD DOOR 2
302	3'-0" X 8'-0" TEMPERED GLASS SHOWER DOOR
303	2'-0" X 8'-0" MODERN TWIN


### WINDOW SCHEDULE

TYPE MARK	WIDTH	HEIGHT	SILL HEIGHT	OPERATION	UNIT	TYPE	QTY
B2	3'-0"	6'-0"	2'-0"	SINGLE HUNG	SINGLE	DIVIDED LITE	6
B8	2'-0"	4'-0"	4'-0"	SINGLE HUNG	SINGLE	DIVIDED LITE	2
D9	3'-0"	1'-6"	6'-6"	FIXED	SINGLE	DIVIDED LITE	1
D14	4'-0"	8'-0"	0"	FIXED	SINGLE	DIVIDED LITE	5
F3	3'-0"	7'-0"	1'-0"	SINGLE HUNG	TWIN	DIVIDED LITE	2
H7	3'-0"	3'-0"	8'-0"	FIXED	TWIN	DIVIDED LITE MULLED TO WINDOW BELOW	2
H243	2'-0"	3'-6"	14'-3"	FIXED	SINGLE	DIVIDED LITE	2
H250	3'-0"	4'-0"	4'-0"	FIXED	QUAD	DIVIDED LITE	1
H273	4'-0"	8'-0"	0"	FIXED	SINGLE	DIVIDED LITE	2
H274	5'-0"	4'-0"	4'-0"	FIXED	SINGLE	DIVIDED LITE	1
H276	2'-8"	4'-0"	13'-9"	FIXED	SINGLE	DIVIDED LITE	4
H277	2'-0"	2'-0"	<varies>	FIXED	SINGLE	DIVIDED LITE	5
H278	6'-0"	1'-6"	6'-6"	FIXED	SINGLE	DIVIDED LITE	2

TOTAL PROJECT WINDOWS: 35

### AREA SLAB

LOCATION:	SQ. FT.
1ST FLOOR LIVING:	3,563 SF
BACK PORCH:	714 SF
BRICK POCKET:	164 SF
FRONT PORCH:	180 SF
GARAGE:	798 SF
<b>*TOTAL SLAB:</b>	<b>5,418 SF</b>



COPYRIGHT BY IMAGINATION DESIGNS, LLC 2023

### GENERAL NOTES:

- A.C. VENTS IN MASTER CLOSET.
- ALL SMOKE DETECTORS SHALL BE HARDWIRED.
- ALL WORK SHALL BE IN STRICT ACCORDANCE WITH CITY OR COUNTY BUILDING CODES AND ORDINANCES.
- GENERAL & SUBCONTRACTORS SHALL VERIFY DIMENSIONS AND EXISTING SITE CONDITIONS. STARTING OF WORK SHALL MEAN ACCEPTANCE OF SUCH CONDITIONS.
- LOCATION OF STORM SEWAGE, DRAINAGE, EASEMENTS, AND BUILDING SETBACKS VERIFIED AT JOB SITE PRIOR TO CONSTRUCTION.
- ALL DIMENSIONS ON EXTERIOR WALLS ARE FROM OUTSIDE OF FOUNDATION TO FACE OF STUD OR FACE OF MASONRY TO FACE OF STUD.
- ALL DIMENSIONS ON INTERIOR WALLS ARE FROM FACE OF STUD TO FACE OF STUD.
- ALL DIMENSIONS TO OPENINGS ARE FROM FOUNDATION TO CENTER OF OPENING.
- ALL EXHAUST FANS IN WET AREAS SHALL BE VENTED OUTSIDE THE HOUSE.
- ALL WORK TO CONFORM TO DEED RESTRICTIONS IF APPLICABLE.
- PLANS TO BE REVIEWED BY ARCHITECTURAL CONTROL COMMITTEE.
- IF A/C IS IN ATTIC, A 3/4" PLYWOOD CATWALK SHALL GO FROM ACCESS HOLE TO UNIT, AND UNIT MUST BE WITHIN 20'
- GENERAL AND SUBCONTRACTORS SHALL VERIFY ENGINEERED DRAWINGS AND ARCHITECTURAL DRAWINGS DO NOT HAVE DISCREPANCIES.
- LOCATION OF STORM DRAINAGE, EASEMENTS, AND BUILDING SETBACKS SHALL BE VERIFIED AT JOB SITE PRIOR TO CONSTRUCTION.
- ALL WINDOWS WITHIN 24" OF AN EXTERIOR OR INTERIOR DOOR TO BE TEMPERED GLASS. ALL OTHER TEMPERED GLASS LOCATIONS PER CODES.
- GENERAL AND SUBCONTRACTORS TO VERIFY ALL WINDOWS MEET EGRESS CODES IN APPLICABLE LOCATIONS.
- GENERAL AND SUBCONTRACTORS TO VERIFY SIZING AND LOCATIONS OF ALL APPLIANCES AND COMPONENTS.

